A SYSTEM FOR ASSISTING REGENERATION OF A STORAGE/RELEASE NOx TRAP FOR A MOTOR VEHICLE DIESEL ENGINE

The present invention relates to a system for reducing pollutant emissions associated with the
5 operation of a motor vehicle diesel engine, and more particularly to a system for assisting regeneration of a storage/release NOx trap integrated into an engine exhaust line.

With direct injection diesel engines for motor
10 vehicles, reducing NOx emissions by storage/release DeNOx catalysis is one technical solution envisaged for compliance with the standards relating to this type of pollution, and in particular the EURO IV standards.

To this end, it is envisaged to use a NOx trap
15 adapted to absorb NOx during standard operation of the engine and consisting of barium sulfate, for example.

It is proposed to trigger a transient release stage when the trap is saturated by momentarily switching the engine from the standard mode of operation with a lean
20 mixture to a regeneration mode of operation with a rich mixture in order to produce reducing agents, for example HC and CO, that reduce the NOx, which is then desorbed from the trap, as in a conventional catalytic converter.

However, that causes problems with stable control of
25 the operation of the engine when using a rich mixture over the whole of its range of operation without impacting on driver comfort, combustion noise, etc.

The object of the invention is therefore to solve the above problems.
30 To this end, the invention consists in a system for assisting regeneration of a storage/release NOx trap integrated in an exhaust line of a motor vehicle diesel engine, the system being characterized in that it comprises gas admission means for admitting gas into the
35 engine, means for injecting fuel into the cylinders thereof in the form of at least pilot and main injections, and means for controlling said gas admission

and/or fuel injection means for periodically switching
the engine between a lean-mixture standard operating mode
in which NOx is stored in the trap and a rich-mixture
regeneration operating mode, with at least two pilot

5   injections and one main injection, in which NOx is
released from the trap and the trap is regenerated.

According to other features of the invention:

- the control means are adapted to control the gas
admission means to reduce the quantity of gas admitted

10   into the engine when said engine is in its regeneration
mode of operation;

- the control means are adapted to control the gas
admission means and/or the fuel injection means in
accordance with the standard and regeneration modes of

15   operation for engine loads below a predetermined
threshold value;

- the predetermined load threshold value is defined
by a brake mean effective pressure (bmep) of
approximately 3 bars;

20   - the engine is associated with exhaust gas
recirculation means for recirculating exhaust gas to its
inlet, and the control means are adapted to regulate the
operation of the recirculation means during operation of
the engine with a rich mixture;

25   - the two pilot injections are triggered in a
crankshaft angle range from approximately 50° to
approximately 5° ahead of the top dead centre point of
the cylinder concerned and the main injection is
triggered in an undercalibrated range up to a crankshaft

30   angle of approximately 35° after the top dead centre
point;

- the control means are adapted to control the gas
admission means and/or the injection means to operate the
engine with a lean mixture for approximately 60 seconds

35   and a rich mixture for approximately 2 seconds.

The invention will be better understood on reading
the following description, which is given by way of

example only and with reference to the appended drawings, in which:

- Figures 1 and 2 show the NOx storage and release stages in a trap included in a system of the invention;

5   - Figure 3 shows the operation of fuel injection means used in a system of the invention; and

- Figure 4 is a block diagram of the structure of a system of the invention.

As indicated above, the invention relates to a

10   system for assisting regeneration of a storage/release NOx trap integrated in an exhaust line of a motor vehicle diesel engine.

Figures 1 and 2 show the storage and release stages.

As also indicated, the NOx trap absorbs NOx during

15   standard operation of the engine with a lean mixture, whereas in a regeneration mode of operation with a rich mixture NOx is released and treated by producing reducing agents such as HC and CO, that reduce NOx, which is then desorbed from the trap as in a conventional catalytic

20   converter.

However, and as indicated above, this leads to the problem of stable operation of a diesel engine when using a rich mixture over the whole of the engine range without impacting on driver comfort, combustion noise, etc.

25   Switching to a stoichiometric or rich mixture is necessary for purging the NOx trap, and also for desulfating it, as sulfur in the fuel poisons the trap.

This operation takes longer than purging, which takes only a few seconds, and is therefore even more

30   difficult to manage.

Under such circumstances, assisting the regeneration of a storage/release NOx trap necessitates the development of a specific multiple injection strategy applicable over the whole of the engine range and based

35   on a plurality of engine parameters.

The injection strategy must:

- enable operation at a richness close to 1;

- produce CO in sufficient quantities, since this is the preferred reducing agent;

       - limit the level of O_2;

       - limit the level of HC;

5   - conform to smoke level criteria;

       - conform to exhaust gas temperature criteria for reasons of mechanical strength; and, finally

       - conform to criteria in respect of services provided to end users, namely driver comfort and engine

10 operating noise.

To this end, the present invention proposes to improve the stability and noise characteristics of combustion at predetermined load points of the engine by applying an injection strategy employing two pilot

15 injections and one main injection, as shown in Figure 3.

Applying the two pilot injections retards the main injection to satisfy the criteria of NOx trap regeneration.

Moreover, exhaust gas recirculation (EGR) can be

20 regulated to conform to the NOx trap regeneration criteria over all these points.

At the predetermined load points, for example for a brake mean effective pressure (bmep) less than about 3 bars, the strategy employing two pilot injections

25 therefore satisfies the NOx trap regeneration criteria, since it significantly reduces combustion instabilities at those points, because of the phasing of the two pilot injections, reduces noise, also because of the phasing of the two pilot injections, retards the main injection, and

30 finally generates an engine map for regeneration of the NOx trap based on a unique strategy.

As indicated above, that strategy may be applied at predetermined operating load points of the engine, to regulate EGR.

35 This is represented in Figure 3, which shows the two pilot injections 1 and 2 and the main injection 3.

The two pilot injections can be triggered in a

crankshaft angle range from approximately 50° to approximately 5° ahead of the top dead centre point of the cylinder concerned, and the main injection can be triggered in an undercalibrated range up to a crankshaft

5   angle of approximately 35° after the top dead centre point.

Figure 4 shows a motor vehicle diesel engine 4 whose outlet is connected to an exhaust line 5 in which a NOx trap 6 is integrated.

10   The engine is also associated with air admission means 7 including means 8 for adjusting the quantity of air admitted.

The engine is also associated with means 9 for recirculating exhaust gases to its inlet associated with

15   means 10 for controlling the circulation of the gas.

The exhaust gas recirculation (EGR) means are therefore connected between the outlet and the inlet of the engine to recirculate the exhaust gases.

The adjustment means 8 and the control means 10 can

20   comprise valves in the conventional way.

The engine is also associated with means 11 for injecting fuel into its cylinders in the form of pilot injections and main injections, as already indicated, such means having any appropriate structure.

25   The various means, i.e. the exhaust gas recirculation means, the air admission means and the injection means, are controlled by control means 12 comprising any appropriate computer receiving as input, for example, engine rotation speed information and

30   injection pressure information from corresponding data acquisition means 13 and 14, respectively.

The control means 11 may periodically switch between the standard operating mode with a lean mixture that stores NOx in the trap and the regeneration mode of

35   operation with a rich mixture that releases NOx from the trap and thereby regenerates the trap, the engine 4 operating with a lean mixture for approximately 60

seconds and a rich mixture for approximately 2 seconds, for example. The control means 12 then operate on the air admission means 7 for admitting air into the engine 4 and the injection means 11 for injecting fuel into its

5   cylinders, to switch the engine periodically from the lean-mixture standard mode of operation to the rich-mixture regeneration mode of operation.

The control means 12 may be adapted to control the gas admission means in order to reduce the quantity of

10   gas admitted into the engine when it is in its regeneration operating mode and to control the injection means in the manner indicated above.

The control means can also be adapted to regulate the operation of the exhaust gas recirculation means 9

15   when the engine is operating with the rich mixture.

Other embodiments can be envisaged, of course.